

PUMPS

CS High-Flow Centrifugal Pumps

PENTAX



Single-impeller centrifugal pumps — medium head, high flow — with 2", 3" and 4" delivery openings. Mainly used in agriculture and applications requiring high-level delivery; flows to 1,600 l/min.

Full technical specification for this product, covering materials of construction, dimensions and standards compliance, is available on request. Contact sales@aavs.co.za and quote the stock code(s) below.

Range

AVAILABLE CONFIGURATIONS · FULL SPEC ON REQUEST

STOCK CODE	SIZE	OPERATION
CS75/2	CS75/2 · 0.59 kW	Single phase
CST75/2	CS75/2 · 0.59 kW	Three phase
CS100/2	CS100/2 · 0.74 kW	Single phase
CST100/2	CS100/2 · 0.74 kW	Three phase
CSB150/2	CSB150/2 · 1.1 kW	Single phase
CSBT150/2	CSB150/2 · 1.1 kW	Three phase
CSB150/2Q	CSB150/2Q · 1.3 kW	Single phase
CSBT150/2Q	CSB150/2Q · 1.3 kW	Three phase
CS150/2	CS150/2 · 1.1 kW	Single phase
CST150/2	CS150/2 · 1.1 kW	Three phase
CS150/2Q	CS150/2Q · 1.5 kW	Single phase
CST150/2Q	CS150/2Q · 1.5 kW	Three phase
CS200/2	CS200/2 · 1.5 kW	Single phase
CST200/2	CS200/2 · 1.5 kW	Three phase
CS200/3	CS200/3 · 1.5 kW	Single phase
CST200/3	CS200/3 · 1.5 kW	Three phase

CS300/3	CS300/3 · 2.2 kW	Single phase
CST300/3	CS300/3 · 2.2 kW	Three phase
CST400/3	CST400/3 · 3 kW	Three phase
CS450/4	CS450/4 · 3 kW	Single phase
CST450/4	CS450/4 · 3 kW	Three phase
CST550/4	CST550/4 · 4 kW	Three phase