


BUTTERFLY VALVES

Butterfly Valves Wafer 316SS Body Spline Shaft EPDM/NBR Liner PN16



Wafer Butterfly Valve Spline Shaft PN16 – 316SS Body, EPDM/NBR Liner

PN16	SABS	JASWIC	BS5155	BS4504	AAVS
------	------	--------	--------	--------	------

316 Stainless Steel Body, Spline Shaft, EPDM or NBR Liner, Lever Handle (300-400mm Gear Box)

PRESSURE RATING	SIZE RANGE	COATING	OPERATION
PN16 (1600 kPa / 16 Bar)	DN50–DN400	Epoxy powder coated body (spline shaft variant)	Lever Handle standard up to 250mm; Gearbox from 300mm up to 1200mm

Specification

- PN16 (1 600 kPa)
- Replaceable EPDM or NBR cartridge liner
- SABS tested, JASWIC compliant
- Semi-lugged or fully lugged body
- 316 stainless steel body
- Spline-shaft drive, blow-out proof
- Designed to BS5155; drilled BS4504
- Lever handle standard to DN250; gearbox DN300–DN1200

Materials of construction

COMPONENT · MATERIAL GRADE

ITEM	PART	MATERIAL
1	Body	316 Stainless Steel
2	Liner / Seat	EPDM or NBR
3	Shaft	Spline shaft, Stainless Steel 13% Chrome
4	Bushing	Lubrized Bronze or Fibre Vesconit
5	Coating	Epoxy powder coated body (spline shaft variant)

Seat / liner temperature ranges

DIMENSIONS IN MM UNLESS STATED

LINER	WORKING TEMP °C
-------	-----------------

PTFE (Teflon)	+10 to +150
Viton	-23 to +294
Silicone Rubber	-65 to +220

Note: Covers two variants: Spline Shaft PN16 (epoxy-coated cast iron body) and Full Stainless Steel PN16 (316 body and disc).

Range

AVAILABLE CONFIGURATIONS · FULL SPEC ON REQUEST

STOCK CODE	SIZE	PN
BVSSF-050	50mm	PN16
BVSSF-065	65mm	PN16
BVSSF-080	80mm	PN16
BVSSF-100	100mm	PN16
BVSSF-125	125mm	PN16
BVSSF-150	150mm	PN16
BVSSF-200	200mm	PN16
BVSSF-250	250mm	PN16
BVSSF-300	300mm	PN16
BVSSF-350	350mm	PN16
BVSSF-400	400mm	PN16