

SGI PIPE FITTINGS

Equal Tee

SANS 52854:2007

AAVS

AAVS SGI Fittings for UPVC Pipe. Equal Tee PN25. Bitumen Dipped SG Iron (FSGI) and FBE Coated SG Iron (FSGF) variants.


PRESSURE

PN25

SIZE RANGE

DN63–DN250

Full technical specification for this product, covering materials of construction, dimensions and standards compliance, is available on request. Contact sales@aavs.co.za and quote the stock code(s) below.

Range

AVAILABLE CONFIGURATIONS · FULL SPEC ON REQUEST

STOCK CODE	SIZE	PN	MATERIAL
FSGI-ET-063	63mm	PN25	Bitumen Dipped
FSGF-ET-063	63mm	PN25	FBE Coated
FSGI-ET-075	75mm	PN25	Bitumen Dipped
FSGF-ET-075	75mm	PN25	FBE Coated
FSGI-ET-090	90mm	PN25	Bitumen Dipped
FSGF-ET-090	90mm	PN25	FBE Coated
FSGI-ET-110	110mm	PN25	Bitumen Dipped
FSGF-ET-110	110mm	PN25	FBE Coated
FSGI-ET-160	160mm	PN25	Bitumen Dipped
FSGF-ET-160	160mm	PN25	FBE Coated
FEGI-ET-200	200mm	PN25	Bitumen Dipped
FSGF-ET-200	200mm	PN25	FBE Coated
FSGI-ET-250	250mm	PN25	Bitumen Dipped
FSGF-ET-250	250mm	PN25	FBE Coated