

SGI PIPE FITTINGS

Flange Adaptors

SANS 52854:2007

AAVS

AAVS SGI Fittings for UPVC Pipe. Flange Adaptors PN16. Bitumen Dipped SG Iron (FSGI) and FBE Coated SG Iron (FSGF) variants.

STOCK CODES	SIZE RANGE	PRESSURE	FROM
18	DN50–DN315	PN16	R 230

Full range & pricing

AAVS LIST PRICE · EXCL. VAT

STOCK CODE	SIZE	PN	MATERIAL	PRICE
FSGF-FA-050-UNI	50mm	PN16	FBE Coated	R 261
FSGI-FA-050-UNI	50mm	PN16	Bitumen Dipped	R 230
FSGF-FA-063-UNI	63mm	PN16	FBE Coated	R 302
FSGI-FA-063-UNI	63mm	PN16	Bitumen Dipped	R 266
FSGF-FA-075-UNI	75mm	PN16	FBE Coated	R 369
FSGI-FA-075-UNI	75mm	PN16	Bitumen Dipped	R 324
FSGF-FA-090-UNI	90mm	PN16	FBE Coated	R 423
FSGI-FA-090-UNI	90mm	PN16	Bitumen Dipped	R 365
FSGF-FA-110-UNI	110mm	PN16	FBE Coated	R 495
FSGI-FA-110-UNI	110mm	PN16	Bitumen Dipped	R 423
FSGF-FA-160-UNI	160mm	PN16	FBE Coated	R 941
FSGI-FA-160-UNI	160mm	PN16	Bitumen Dipped	R 842
FSGF-FA-200-UNI	200mm	PN16	FBE Coated	R 1,436
FSGI-FA-200-UNI	200mm	PN16	Bitumen Dipped	R 1,283
FSGF-FA-250-UNI	250mm	PN16	FBE Coated	R 2,052
FSGI-FA-250-UNI	250mm	PN16	Bitumen Dipped	R 1,769
FSGF-FA-315-UNI	315mm	PN16	FBE Coated	R 3,465
FSGI-FA-315-UNI	315mm	PN16	Bitumen Dipped	R 3,047