

SGI PIPE FITTINGS

Reducing Bush

SANS 52854:2007

AAVS



AAVS SGI Fittings for UPVC Pipe. Reducing Bush PN25. Bitumen Dipped SG Iron (FSGI) and FBE Coated SG Iron (FSGF) variants.

PRESSURE

PN25

SIZE RANGE

DN63–DN250

Full technical specification for this product, covering materials of construction, dimensions and standards compliance, is available on request. Contact sales@aavs.co.za and quote the stock code(s) below.

Range

AVAILABLE CONFIGURATIONS · FULL SPEC ON REQUEST

STOCK CODE	SIZE	PN	MATERIAL
FSGI-RB-63-50	63-50	PN25	Bitumen Dipped
FSGF-RB-63-50	63-50	PN25	FBE Coated
FSGI-RB-75-50	75-50	PN25	Bitumen Dipped
FSGF-RB-75-50	75-50	PN25	FBE Coated
FSGI-RB-75-63	75 - 63	PN25	Bitumen Dipped
FSGF-RB-75-63	75 - 63	PN25	FBE Coated
FSGI-RB-90-63	90 - 63	PN25	Bitumen Dipped
FSGF-RB-90-63	90 - 63	PN25	FBE Coated
FSGI-RB-90-75	90 - 75	PN25	Bitumen Dipped
FSGF-RB-90-75	90 - 75	PN25	FBE Coated
FSGI-RB-110-63	110 - 63	PN25	Bitumen Dipped
FSGF-RB-110-63	110 - 63	PN25	FBE Coated
FSGI-RB-110-75	110 - 75	PN25	Bitumen Dipped
FSGF-RB-110-75	110 - 75	PN25	FBE Coated
FSGI-RB-110-90	110 - 90	PN25	Bitumen Dipped

FSGF-RB-110-90	110 - 90	PN25	FBE Coated
FSGI-RB-160-90	160 - 90	PN25	Bitumen Dipped
FSGF-RB-160-90	160 - 90	PN25	FBE Coated
FSGI-RB-160-110	160 - 110	PN25	Bitumen Dipped
FSGF-RB-160-110	160 - 110	PN25	FBE Coated
FSGI-RB-200-110	200 - 110	PN25	Bitumen Dipped
FSGF-RB-200-110	200 - 110	PN25	FBE Coated
FSGI-RB-200-160	200 - 160	PN25	Bitumen Dipped
FSGF-RB-200-160	200 - 160	PN25	FBE Coated
FSGI-RB-250-160	250 - 160	PN25	Bitumen Dipped
FSGF-RB-250-160	250 - 160	PN25	FBE Coated
FSGI-RB-250-200	250 - 200	PN25	Bitumen Dipped
FSGF-RB-250-200	250 - 200	PN25	FBE Coated