

SGI PIPE FITTINGS

Socketed Reducer

SANS 52854:2007

AAVS

AAVS SGI Fittings for UPVC Pipe. Socketed Reducer PN25. Bitumen Dipped SG Iron (FSGI) and FBE Coated SG Iron (FSGF) variants.

STOCK CODES

22

SIZE RANGE

DN75–DN250

PRESSURE

PN25

FROM

R 311

Full range & pricing

AAVS LIST PRICE · EXCL. VAT

STOCK CODE	SIZE	PN	MATERIAL	PRICE
FSGF-SR-75-63	75-63mm	PN25	FBE Coated	R 342
FSGI-SR-75-63	75-63mm	PN25	Bitumen Dipped	R 311
FSGF-SR-90-63	90-63mm	PN25	FBE Coated	R 374
FSGF-SR-90-75	90-75mm	PN25	FBE Coated	R 405
FSGI-SR-90-63	90-63mm	PN25	Bitumen Dipped	R 338
FSGI-SR-90-75	90-75mm	PN25	Bitumen Dipped	R 360
FSGF-SR-110-75	110-75mm	PN25	FBE Coated	R 518
FSGF-SR-110-90	110-90mm	PN25	FBE Coated	R 522
FSGI-SR-110-75	110-75mm	PN25	Bitumen Dipped	R 455
FSGI-SR-110-90	110-90mm	PN25	Bitumen Dipped	R 464
FSGF-SR-160-110	160-110mm	PN25	FBE Coated	R 855
FSGF-SR-160-90	160-90mm	PN25	FBE Coated	R 684
FSGI-SR-160-110	160-110mm	PN25	Bitumen Dipped	R 770
FSGI-SR-160-90	160-90mm	PN25	Bitumen Dipped	R 612
FSGF-SR-200-110	200-110mm	PN25	FBE Coated	R 1,386
FSGF-SR-200-160	200-160mm	PN25	FBE Coated	R 1,760
FSGI-SR-200-110	200-110mm	PN25	Bitumen Dipped	R 1,238
FSGI-SR-200-160	200-160mm	PN25	Bitumen Dipped	R 1,562
FSGF-SR-250-160	250-160mm	PN25	FBE Coated	R 1,778
FSGF-SR-250-200	250-200mm	PN25	FBE Coated	R 2,034
FSGI-SR-250-160	250-160mm	PN25	Bitumen Dipped	R 1,584

FSGI-SR-250-200

250-200mm

PN25

Bitumen Dipped

R 1,809