

SGI PIPE FITTINGS

Straight Connector / Repair Coupling

SANS 52854:2007

AAVS

AAVS SGI Fittings for UPVC Pipe. Straight Connector / Repair Coupling PN25. Bitumen Dipped SG Iron (FSGI) and FBE Coated SG Iron (FSGF) variants.

STOCK CODES

14

SIZE RANGE

DN63–DN250

PRESSURE

PN25

FROM

R 225

Full range & pricing

AAVS LIST PRICE · EXCL. VAT

STOCK CODE	SIZE	PN	MATERIAL	PRICE
FSGF-SC-063	63mm	PN25	FBE Coated	R 306
FSGI-SC-063	63mm	PN25	Bitumen Dipped	R 225
FSGF-SC-075	75mm	PN25	FBE Coated	R 428
FSGI-SC-075	75mm	PN25	Bitumen Dipped	R 279
FSGF-SC-090	90mm	PN25	FBE Coated	R 545
FSGI-SC-090	90mm	PN25	Bitumen Dipped	R 374
FSGF-SC-110	110mm	PN25	FBE Coated	R 716
FSGI-SC-110	110mm	PN25	Bitumen Dipped	R 446
FSGF-SC-160	160mm	PN25	FBE Coated	R 1,377
FSGI-SC-160	160mm	PN25	Bitumen Dipped	R 887
FSGF-SC-200	200mm	PN25	FBE Coated	R 1,485
FSGI-SC-200	200mm	PN25	Bitumen Dipped	R 1,323
FSGF-SC-250	250mm	PN25	FBE Coated	R 2,241
FSGI-SC-250	250mm	PN25	Bitumen Dipped	R 1,994