

SGI PIPE FITTINGS

Unequal Tee

SANS 52854:2007

AAVS



AAVS SGI Fittings for UPVC Pipe. Unequal Tee PN25. Bitumen Dipped SG Iron (FSGI) and FBE Coated SG Iron (FSGF) variants.

PRESSURE

PN25

SIZE RANGE

DN75–DN250

Full technical specification for this product, covering materials of construction, dimensions and standards compliance, is available on request. Contact sales@aavs.co.za and quote the stock code(s) below.

Range

AVAILABLE CONFIGURATIONS · FULL SPEC ON REQUEST

STOCK CODE	SIZE	PN	MATERIAL
FSGI-UT-75 - 50	75-50mm	PN25	Bitumen Dipped
FSGF-UT-75 - 50	75-50mm	PN25	FBE Coated
FSGI-UT-75 - 63	75-63mm	PN25	Bitumen Dipped
FSGF-UT-75 - 63	75-63mm	PN25	FBE Coated
FSGI-UT-90 - 63	90-63mm	PN25	Bitumen Dipped
FSGF-UT-90 - 63	90-63mm	PN25	FBE Coated
FSGI -UT-90- 75	90-75mm	PN25	Bitumen Dipped
FSGF -UT-90- 75	90-75mm	PN25	FBE Coated
FSGI-UT-110-63	110-63mm	PN25	Bitumen Dipped
FSGF-UT-110-63	110-63mm	PN25	FBE Coated
FSGI-UT-110-75	110-75mm	PN25	Bitumen Dipped
FSGF-UT-110-75	110-75mm	PN25	FBE Coated
FSGI-UT-110-90	110-90mm	PN25	Bitumen Dipped
FSGF-UT-110-90	110-90mm	PN25	FBE Coated
FSGI-UT-160-90	160-90mm	PN25	Bitumen Dipped

FSGF-UT-160-90	160-90mm	PN25	FBE Coated
FSGI-UT-160-110	160-110mm	PN25	Bitumen Dipped
FSGF-UT-160-110	160-110mm	PN25	FBE Coated
FSGI -UT-200-90	200-90mm	PN25	Bitumen Dipped
FSGF -UT-200-90	200-90mm	PN25	FBE Coated
FSGI-UT-200-110	200-110mm	PN25	Bitumen Dipped
FSGF-UT-200-110	200-110mm	PN25	FBE Coated
FSGI-UT-200-160	200-160mm	PN25	Bitumen Dipped
FSGF-UT-200-160	200-160mm	PN25	FBE Coated
FSGI-UT-250-160	250-160mm	PN25	Bitumen Dipped
FSGF-UT-250-160	250-160mm	PN25	FBE Coated
FSGI-UT-250-200	250-200mm	PN25	Bitumen Dipped
FSGF-UT-250-200	250-200mm	PN25	FBE Coated